

Machined aluminum dual axis gimbal. Adjustable and lockable
Trim fixture designed to conceal internal hardware
Trimless fixture features a proprietary aluminum mudding flange
Lumen range of 1000lm to 2200lm
2 SDCM, Citizen LED source available in 30K and 35K (80+ CRI)
Universal voltage, 0-10V integral driver with 100-1% dimming range



10 DAY QUICKSHIP
Max Order Size: 50 pcs

ORDERING INFORMATION										
PROJECT:								TYPE:		
CATALOG #:								DATE:		
CAT. NO	LUME	N OUTPUT	CRI	COLOR TEMP	BEAM	VOLTAGE	DRIVER			
3GQ-RC1	<b>15 -</b> 15	000 LUMENS 500 LUMENS 200 LUMENS	<b>\$80 -</b> 80+CRI	<b>30K -</b> 3000K		<b>UNY-</b> 120/277V	<b>DIM -</b> 0-10V (100-1%)			
FLANGE TYPE		GIMBAL FINISH		HOUSING INTERIOR	HOUSING TYPE			OPTIONS		
WT - WHITE XTR - TRIMLESS		NG - NATURAL ALUMINUM BG - BLACK WG - WHITE		BK - BLACK	NC - NEW CONSTRUCTION (NON-IC		N-IC)	CP - CHICAGO PLENUM  SF70 - SOFTENING LENS  HXB70 - BLACK HEXCELL LOUVER  BH - C-CHANNEL BAR HANGERS  Maximum 3 optical accessories		

Refer to standard specification sheets for complete details. Please note that only options shown above qualify for 10 day 3GQ program and the standard specification of the standard spe









## 1 LIGHT MADISON - TRIM & TRIMLESS


## TRIM HOUSING OPTIONS

NC - New Construction (Non-IC)


IC - IC Housing (2200lm max)

**CP -** Chicago Plenum Housing

## 



 4.93"	



**DUAL AXIS ADJUSTABILITY** 

A

45°

45°

С

45°

LUMEN OUTPUT

Up to 2200lm

## TRIMLESS HOUSING OPTIONS

NC - New Construction (Non-IC)

IC - IC Housing (2200lm max)

**CP** - Chicago Plenum Housing

