

SURFACE LINEAR KUBO

3G-SLKU6 6" SURFACE MOUNTED

3G
LIGHTING



Pendant Linear Kubo



Recessed Linear Kubo



24" Surface Kubo



24" Pendant Kubo

FEATURES

CONSTRUCTION

- White sandblasted acrylic diffuser. Fabricated with mitered corners
- Fixture collar and mounting canopy fabricated in steel with powder coated finish
- Modified configurations available upon request

ELECTRICAL

- Standard 120-277V dimmable driver with 100-1% dimming range
- 85% efficiency and 0.9 power factor
- Lutron driver options available with 100-1% dimming range
- eLdoLED Dali driver available with 100-1% dimming range

LED SYSTEM

- Available in 27K, 30K, 35K, and 40K
- Average rated life > 50,000 hours
- Color consistency < 3 SDCM
- CRI > 80 for 27K, 30K, 35K, and 40K

LUMEN MAINTENANCE

- L70 at 50,000 hours

MOUNTING

- Suitable for ceiling and wall applications
- Fixture mounts to a standard junction box

FINISH

- Standard polyester powder coated matte white finish. Optional matte silver finish

LABELS

- ETL listed. Suitable for dry or damp locations (indoor use)

WARRANTY



- 5 Year limited warranty

PROJECT

TYPE

DATE

CATALOG #



ORDERING INFORMATION

CAT. NO	LENGTH	LED SYSTEM	COLOR TEMP	VOLTAGE	DRIVER	FINISH
3G-SLKU6	24 - 24"	L2 - STANDARD OUTPUT	27K - 2700K	120 - 120V	DIM - 0-10V (STANDARD - 100-1%)	WH - WHITE (STANDARD)
	36 - 36"	L4 - HIGH OUTPUT	30K - 3000K	277 - 277V	DHL - LUTRON (3-WIRE - 100-1%)	SV - SILVER
	48 - 48"		35K - 3500K	347 - 347V (0-10V ONLY)	DHL2 - LUTRON (ECOSYSTEM - 100-1%)	
	60 - 60"		40K - 4000K		DALI - DIMMING	
	96 - 94"					
3G-SLKU6						

ORDERING EXAMPLE

3G-SLKU6-24-L2-30K-120-DIM-WH

Copyright 2016 3G Lighting.
P: 905-850-2305 F: 905-851-6490 | TF: 888-448-0440
3G reserves the right to change, without notice, specifications or materials for product improvement.



SURFACE LINEAR KUBO


3G-SLKU6
6" SURFACE MOUNTED



PERFORMANCE CHART (based on 3500K)

LENGTH	LED SYSTEM	SYSTEM WATTS	DELIVERED LUMENS	EFFICACY LM/W	IES FILES
24"	L2 - STANDARD OUTPUT	11W	904	82	DOWNLOAD
	L4 - HIGH OUTPUT	19W	1544	81	DOWNLOAD
36"	L2 - STANDARD OUTPUT	16W	1351	84	DOWNLOAD
	L4 - HIGH OUTPUT	28W	2305	82	DOWNLOAD
48"	L2 - STANDARD OUTPUT	22W	1871	85	DOWNLOAD
	L4 - HIGH OUTPUT	37W	3193	86	DOWNLOAD
60"	L2 - STANDARD OUTPUT	27W	2372	88	DOWNLOAD
	L4 - HIGH OUTPUT	46W	4047	88	DOWNLOAD
94"	L2 - STANDARD OUTPUT	43W	3712	86	DOWNLOAD
	L4 - HIGH OUTPUT	73W	6333	87	DOWNLOAD

MOUNTING



NOTES