

3G-WDL45RF

4" WALL CYLINDER
DIRECT OR INDIRECT
7" AND 11" HEIGHT



4" high performance wall mounted downlight cylinder
Standard 95+ CRI LED system with up to 126 LPW
Delivered lumen range up to 2856lm at 95+ CRI
Available with direct or indirect distribution
Extruded aluminum housing with powder coated finish
Regressed LED source for enhanced glare control
Companion to 3G-DL45R series downlight family


DIRECT - 7IN



DIRECT - 11IN




INDIRECT - 7IN



INDIRECT - 11IN



OPTICS




PERFORMANCE

LUMEN OUTPUT	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
1000	1000	9.1	110
1500	1500	14.0	108
2000	2000	19.0	105
2500	2500	24.2	103

BASED ON 95+ CRI, 3500K, 20D OPTIC WITH SOFTENING LENS
Lumen output and actual wattage may vary +/- 5%

DIMENSIONS



3G LIGHTING

3G-WDL45RF
4" WALL CYLINDER, DIRECT AND INDIRECT, 7" AND 11" HEIGHT

ORDERING INFORMATION

PROJECT:		**TYPE:**			
CATALOG#:		**DATE:**		**QTY:**	

CAT. NO	DISTRIBUTION	FIXTURE HEIGHT	LUMEN OUTPUT (DELIVERED LUMENS)
3G-WDL45RF	**D -** DIRECT **I -** INDIRECT	**7H -** 7" HEIGHT * **11H -** 11" HEIGHT *7H available up to 2000lm (DIM & LE options)	**10 -** 1000 LUMENS **15 -** 1500 LUMENS **20 -** 2000 LUMENS **25 -** 2500 LUMENS All lumen outputs are delivered lumens at 95+ CRI

CRI	COLOR TEMP	BEAM ANGLE	VOLTAGE
H95 - 95+ CRI	**27K -** 2700K **30K -** 3000K **35K -** 3500K **40K -** 4000K	**10D -** 10° [1] **20D -** 20° **40D -** 40° **60D -** 60° **90D -** 90° 90D optic supplied with lens Not available with other lens options	**UNV -** 120/277V **120 -** 120V **347 -** 347V [2]

DRIVER	HOUSING FINISH	INSERT FINISH	OPTIONS
DIM - 0-10V (100-1%) **LE -** PHASE DIM [3] (TRIAC/ELV, 100-1%) **D01 -** 0-10V (100-0.1%) **DALI -** DALI (100-1%) [4] **DHL2 -** LUTRON HI-LUME [5] (1% ECOSYSTEM) **DMX -** DMX (100-0%) [5]	**WH -** WHITE **BK -** BLACK **SV -** SILVER **CF -** CUSTOM COLOR	**WI -** WHITE **BI -** BLACK **SI -** SILVER **CI -** CUSTOM COLOR	**SF -** SOFTENING LENS * (SUPPLIED STANDARD) **LS -** LINEAR SPREAD LENS **SB -** SANDBLASTED LENS *Softening lens not provided with 90D optic Maximum 1 optical accessory

1 10D optic available up to 2000lm
2 347 available in "DIM" 0-10V. Not available with 7H model
3 Phase dimming options available in 120V only
4 DALI-2 (Type 6) provided as standard. Consult factory for DALI Type 8 option
5 DHL2, and DMX available with 11" model only

PERFORMANCE

LUMEN OUTPUT	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
1000	1000	9.1	110
1500	1500	14.0	108
2000	2000	19.0	105
2500	2500	24.2	103

BASED ON 95+ CRI, 3500K, 20D OPTIC WITH SOFTENING LENS
Lumen output and actual wattage may vary +/- 5%

MULTIPLIERS

BEAM ANGLE	
10D	1.07
20D	1.12
40D	1.00
60D	1.04
90D	0.96

COLOR TEMP	
2700K	0.98
3000K	1.00
3500K	1.00
4000K	1.02

HOUSING
Extruded aluminum housing with powder coated finish

BEVELED INSERT
4" aperture with regressed LED source for enhanced glare control
Cast aluminum insert with matte powder coated finish

OPTICS
Proprietary anodized, aluminum reflectors
Available in 10°, 20°, 40°, 60° and 90°
Reflectors are field replaceable (10° reflector not interchangeable)
Softening lens supplied standard

LISTING
ETL listed and conforms to UL1598 standard
Certified to CSA22.2 NO.250.0.
Rated for indoor dry or damp locations

WARRANTY
5 year limited warranty
LED system rated for operation in ambient environments up to 25°C

ELECTRICAL
Standard 0-10V, constant current drivers with 100-1% dimming range and >0.9 power factor
Standard 120/277V universal voltage with several driver options
Integral drivers are easily accessible through fixture aperture
7" models include 0-10V drivers that operate only with dimmers that sink current (not designed for source current)
Compatible 0-10V dimmers for all 7" height models listed below:
Lutron NFTV, **Lutron** DVTV , **Lutron** DVSTV, **Lutron** VIVE RMJS-8TN, **Leviton** IP710-DLZ, **Philips** SR1200ZTUNV, **Cooper** SF10P

LED SYSTEM
Standard 95+ CRI
Color consistency <2 SDCM
Available in 27K, 30K, 35K, and 40K
L90 > 50,000 hours

MOUNTING
Square machined aluminum canopy with powder coated finish
Bracket and hardware mount to standard 4" octagonal junction box
Fixture weight: +/- 4.25 lbs

Declare® is a product transparency program administered by the International Living Future Institute (ILFI), providing standardized disclosure of product ingredients, manufacturing location, service life, end-of-life pathways, and Living Building Challenge compliance status.

PRODUCT FAMILY COVERAGE — CYLINDERS

Cylinder luminaires for surface, pendant, and wall-mounted applications. Available with multiple beam angles, lumen packages, and 95+ CRI as standard. Options include low-glare optical control, UGR-rated configurations, multiple mounting and canopy systems, adjustable downlight modules, dual-axis gimbals, and low-glare multicell optics.

LBC RED LIST FREE

This product family carries a Declare® designation of LBC Red List Free, the highest designation within the Declare program. Products with this designation contain no intentionally added Red List chemicals above applicable Declare reporting thresholds and have been evaluated against the Living Building Challenge Red List.

Red List Free
INTERNATIONAL LIVING FUTURE INSTITUTE™

BUILDING CERTIFICATION PROGRAMS

Material transparency documentation is increasingly requested as part of building certification programs and owner standards. Declare labels may be used as supporting documentation for project teams pursuing:

- Living Building Challenge (LBC)
- WELL Building Standard™ v1
- WELL Building Standard™ v2
- LEED®
- Other material disclosure and material health initiatives

Project certification requirements are determined at the building level and should be evaluated by the project team.

Declare.℠

Cylinders
3G Lighting

Final Assembly: Woodbridge, Ontario, Canada
Life Expectancy: 7+ Year(s)
End of Life Options: Recyclable (95%), Landfill (5%)

Ingredients:

Aluminum UNS A96063; Steel, cold roll UNS G10080; Copper UNS C11000; Pulp, cellulose; Aluminum diethylphosphinate; Benzene, ethenyl-, polymer with 1,3-butadiene, hydrogenated; Distillates (petroleum), hydrotreated heavy naphthenic; Polypropylene; Paper; Tin, Organic; Starch, base-hydrolyzed, borated; 2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-; Vinyl acetate; Phosphorus; Iron; Zinc; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-

Living Building Challenge Criteria: Compliant

I-13 Red List:
■ LBC Red List Free
□ LBC Red List Approved
□ Declared

% Disclosed: 100% at 100ppm
VOC Content: Not Applicable

I-10 Interior Performance: Not Applicable
I-14 Responsible Sourcing: Not Applicable

GLG-0002
EXP. 01 JUN 2027
Original Issue Date: 2026

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare