

3.3" WALL WASH PENDANT


STEM PENDANT MOUNT




THE IMAGES SHOWN ARE FOR ILLUSTRATION ONLY AND MAY NOT BE AN EXACT REPRESENTATION OF THE PRODUCT

COMPONENTS


STANDARD CANOPY




CONDUIT FEED CANOPY



POWER CANOPY




4" OCTAGONAL J-BOX REQUIRED FOR INSTALLATION



JUNCTION BOX (BY OTHERS)

SUITABLE FOR SLOPED CEILING








INSTRUCTION KEY










INFORMATION

- ⚠ ADDITIONAL
- ⓘ ATTENTION
- ⚡ POWER ON
- ⓧ POWER OFF



INSTALLATION SHOULD ONLY BE PERFORMED BY A CERTIFIED ELECTRICIAN
REFER TO LOCAL/NATIONAL CODES FOR PROPER INSTALLATION
FAILURE TO FOLLOW INSTALLATION INSTRUCTION MAY VOID THE WARRANTY
DO NOT TOUCH LEDS. LEDS MUST BE PROTECTED FROM MECHANICAL STRESS OR DEBRIS
TURN OFF POWER DURING INSTALLATION OR SERVICING









6B




CANOPY IS SUITABLE FOR
MAXIMUM 3 CONDUIT FEEDS




1 CONDUIT FEED CANOPY



2




3




ENSURE CANOPY CLIPS ALIGN WITH BRACKET

4




CONNECT CANDUIT CANOPY AND FEED
JUNCTION BOX WIRES THROUGH HOLE

5



! CANOPY IS SUITABLE FOR
MAXIMUM 3 CONDUIT FEEDS

6 POWER CANOPY




WIRING LEGEND


BLACK	HOT/LINE
WHITE	NEUTRAL
GREEN	GROUND
ORANGE	(DIM-)
PINK	(DIM-)
BLUE	(DIM-)
PURPLE	(DIM+)
RED	(DIM+)

! MAKE WIRING CONNECTIONS

7




8




! CUT STEM LENGTH
IF APPLICABLE


9



10




11




 MAKE WIRING CONNECTIONS

12




13




DRIVER SERVICING

1




2




LED SERVICING

1




DISCONNECT LED WIRES AND REMOVE LED INSERT

2



LOOSEN HEATSINK BRACKET SCREW


3




TWIST AND REMOVE LED ASSEMBLY
FROM REFLECTOR

DRIVER SERVICING

1



2



3

