


# WALL LINIA

**3G-2WLI-D**  
**2" WALL**  
DIRECT

**3G**  
LIGHTING



DD1



DD2



**Recessed Linia**



**Surface Linia**



**Pendant Linia**

## FEATURES

### CONSTRUCTION

- 2" extruded aluminum housing with machined aluminum end caps
- Individual units and continuous runs in 1' increments
- 24 gauge LED reflector with high reflectance white powder coated finish
- Extruded acrylic lens with satin finish available in flush and drop lens options

### ELECTRICAL

- Standard 120-277V, 0-10V dimmable driver with 100-1% dimming range
- 85% efficiency and 0.9 power factor
- Lutron driver options available with 100-1% dimming range
- eLdoLED Dali driver available with 100-1% dimming range
- Emergency Battery: 90 minutes

### LED SYSTEM

- Available in 27K, 30K, 35K, and 40K
- Average rated life of >50,000 hours
- Color consistency 3 SDCM
- CRI>80 for 27K, 30K, 35K, and 40K

### LUMEN MAINTENANCE

- L70 at >50,000 hours

### MOUNTING

- Suitable for wall mount applications (2"x4" junction box)
- Fixture is secured to mounting brackets that fasten directly to the wall

### FINISH

- Standard polyester powder coated matte white finish. Optional matte silver and black finish


### LABELS

- ETL listed. Suitable for dry or damp locations (indoor use)

### WARRANTY

- 5 Year limited warranty

<b>PROJECT</b>	<b>TYPE</b>	<b>DATE</b>
<b>CATALOG #</b>		





**LENS OPTIONS**

**FL - FLUSH LENS**

**DD1 - 1" DROP LENS**

**DD2 - 2" DROP LENS**



**ORDERING INFORMATION**

CAT. NO	LED SYSTEM	COLOR TEMP	VOLTAGE	DRIVER
<b>3G-2WLI-D</b>	<b>L1</b> - LOW OUTPUT	<b>27K</b> - 2700K	<b>120</b> - 120V	<b>DIM</b> - 0-10V (STANDARD 100-1%)
	<b>L2</b> - STANDARD OUTPUT	<b>30K</b> - 3000K	<b>277</b> - 277V	<b>DHL</b> - LUTRON (3-WIRE-100-1%)
	<b>L4</b> - HIGH OUTPUT	<b>35K</b> - 3500K	<b>347</b> - 347V (0-10V ONLY)	<b>DHL2</b> - LUTRON (ECOSYSTEM-100-1%)
		<b>40K</b> - 4000K		<b>DALI</b> - DALI (100-1%)

<b>3G-2WLI-D</b>				
------------------	--	--	--	--

LENS OPTIONS	FINISH	OPTIONS	LENGTH (FEET)
<b>FL</b> - FLUSH <b>DD1</b> - 1" DROP LENS <b>DD2</b> - 2" DROP LENS	<b>WH</b> - WHITE (STANDARD) <b>SV</b> - SILVER <b>BK</b> - BLACK	<b>EM</b> - EMERGENCY BATTERY (4' SECTION)	<b>S</b> - ___' (STRAIGHT RUN)  Individual units available in 3', 4', 5', or 8', continuous runs available in 1' increments.

--	--	--	--

ORDERING EXAMPLE      **3G-2WLI-D-L2-30K-120-DIM-FL-WH-S-8'**

Copyright 2016 3G Lighting.  
 P: 905-850-2305 F: 905-851-6490 | TF: 888-448-0440  
 3G reserves the right to change, without notice, specifications or materials for product improvement.



# WALL LINIA


**3G-2WLI-D**  
**2" WALL**  
DIRECT



## PERFORMANCE CHART (Based on 3500K, 4' length)

LENS OPTIONS	LED SYSTEM	WATTAGE/FT	LUMENS/FT	EFFICACY (LM/W)	IES FILES
<b>FLUSH</b>	L1 - LOW OUTPUT	3.5W	365	104	<a href="#">DOWNLOAD</a>
	L2 - STANDARD OUTPUT	5.5W	522	95	<a href="#">DOWNLOAD</a>
	L4 - HIGH OUTPUT	9.5W	866	92	<a href="#">DOWNLOAD</a>
<b>1" DROP</b>	L1 - LOW OUTPUT	3.5W	386	110	<a href="#">DOWNLOAD</a>
	L2 - STANDARD OUTPUT	5.5W	535	97	<a href="#">DOWNLOAD</a>
	L4 - HIGH OUTPUT	9.5W	918	97	<a href="#">DOWNLOAD</a>
<b>2" DROP</b>	L1 - LOW OUTPUT	3.5W	383	110	<a href="#">DOWNLOAD</a>
	L2 - STANDARD OUTPUT	5.5W	530	97	<a href="#">DOWNLOAD</a>
	L4 - HIGH OUTPUT	9.5W	910	96	<a href="#">DOWNLOAD</a>

## MOUNTING



## NOTES: